

Synology RackStation RS2211+/RS2211RP+

2U High performance NAS Server Scales up to 22 Drives for Enterprise Users



Synology® RackStation RS2211+/RS2211RP+ offers a high-performance, scalable, and full-featured network attached storage solution that meets the needs of business that requires an efficient way to centralize data protection, simplify data management, and rapidly scale storage capacity with minimal time spent on setup and management. The Synology RS2211+/RS2211RP+ is backed with Synology's 3-year limited warranty.

Highlights

- 166.01 MB/sec Writing, 198.10 MB/sec Reading¹
- Windows® ADS and ACL Support
- iSCSI Support as Virtualization Solution
- Scale up to 22 Drives with Synology RX1211/RX1211RP²
- 2 LAN with Failover and Link Aggregation Support
- Hot-swappable Hard Drive Design
- Running on Synology DiskStation Manager (DSM)

High Performance, High Data Availability

With the Link Aggregation enabled, Synology RS2211+/RS2211RP+ delivers an average 166.01 MB/sec writing speed under RAID 5 configuration in a Windows environment, and 198.10 MB/sec reading. The 2 LAN with failover support and hot-swappable drives will ensure continual service uptime should the drives need replacement or the unexpected LAN failure. Businesses need a strong foundation to face mission-critical tasks so the Synology RS2211+/RS2211RP+ delivers high-performance with high data availability ensuring access when it's needed.

Fit to Business Environment

Windows ADS integration allows the Synology RS2211+/RS2211RP+ to quickly and easily fit in an existing business network environment with no need to recreate users' accounts on the Synology RS2211+/RS2211RP+. The User Home feature minimizes the administrator's effort in creating a private shared folder for a large amount of users.

Windows ACL support on RS2211+/RS2211RP+ provides much finer-grained access control and efficient privilege settings, allowing IT staffs to set up privileges to files and folders on RS2211+/RS2211RP+ through their familiar Windows user interface. The privileges set on Windows ACL will be applied to all access entries, including AFP, FTP, File Station, NFS and WebDAV. The secure privilege offers IT staff peace of mind, no worries about any loopholes.

iSCSI and Virtualization Ready

With the iSCSI support in DSM, the Synology RS2211+/RS2211RP+ provides a seamless storage solution for virtualization servers, such as VMware, Hyper-V, and Citrix. It is the ideal alternative to SAN solution for businesses. Affordable and cost-effective, iSCSI allows SMB users to consolidate storage into data center storage arrays while providing hosts with the illusion of locally-attached disks.

Robust & Affordable Scalability Up to 66 TB

When the storage capacity of the Synology RS2211+/RS2211RP+ is nearing its limits, it can easily be expanded by the Synology RX1211/RX1211RP³. The Synology RS2211+/RS2211RP+ securely connects to the Synology RX1211/RX1211RP with an Infiniband cable, offering high-bandwidth connectivity to further ensure efficiency. The Synology RX1211/RX1211RP can directly expand the existing storage on the Synology RS2211+/RS2211RP+ to a maximum 66 TB capacity.

Full-featured Business Applications

The Synology RS2211+/RS2211RP+ runs on the renowned operating system, Synology DSM, offering comprehensive applications and features designed specifically for SMBs. Comprehensive network protocol support assures seamless file sharing across Windows, Mac, and Linux platforms.

Internet file access is simplified by the encrypted FTP server and the web-based file explorer, Synology File Station. HTTPS, firewall, and IP auto-block support ensure file sharing over the Internet is protected at a high security level.

A wealth of additional features allows the Synology RS2211+/RS2211RP+ to replace several pieces of network hardware. Synology Web Station with support for PHP/MySQL content allows for the hosting of up to 30 websites on a single Synology RS2211+/RS2211RP+. Synology Surveillance Station offers a centralized interface to safeguard the office environments by deploying IP cameras throughout the network. RS2211+/RS2211RP+ features a mail server that can work with mail clients such as Mac Mail or Windows Outlook, and the USB printer sharing capability minimizes businesses' printing cost by sharing printing resources throughout the office.

Energy Efficient Design

Synology RackStations are designed and developed with energy efficiency in mind. Compared with the average PC counterparts, Synology RackStations consume a relatively low amount of power and have the hard drives hibernate when not in use.



All Synology products are produced with RoHS compliant parts and packed with recyclable packing materials. Synology acknowledges the responsibility as a global citizen to continually work to reduce the environmental impact of every product produced.



RS2211+/RS2211RP+

RX1211/RX1211RP

CONNECTIONS & BUTTONS



Technical Specifications

Hardware

- CPU: Dual Core 1.8 GHz, with floating point
- RAM Size: DDR2 1GB
- Internal HDD: 10X 3.5" SATA(II) or 10X 2.5" SATA/SDD
- External HDD Interface: 4X USB ports
- Expansion Interface: 1X Expansion port
- Rail Kit: Synology 2U Rail Kit Sliding (optional)
- Size:
 - RS2211+: 88mm X 445mm X 570mm
 - RS2211RP+: 88mm X 445mm X 570mm
- Weight:
 - RS2211+: 12.2kg
 - RS2211RP+: 14.3kg
- LAN: 2X Gigabit
- Wireless Support*
 - Fan: 4X (80mm X 80mm)
 - Wake on LAN
- Power Recovery
- AC Input Power Voltage: 100V to 240V
- Power Frequency: 50Hz to 60Hz, Single Phase

- Max Internal Capacity: 30TB (10X 3TB hard drives)⁸
- Operating Temperature: 5°C to 35°C (40°F to 95°F)
- Storage Temperature: -10°C to 70°C (15°F to 158°F)
- Relative Humidity: 5% to 95% RH
- Max Operating Altitude: 10,000 feet
- Power Consumption*: 115.5W (Access); 49.5W (HDD Hibernation)
- Certification: FCC Class A, CE Class A

Applications

File Station

- FTP Server**
- Bandwidth Control
 - Custom FTP Passive Port Range
 - Anonymous FTP
 - Transfer Log

Web Station

- Virtual Host (up to 30 websites)
- PHP/MySQL
- Alternative HTTP Error Page
- 3rd-Party Applications Support

Surveillance Station

- Default IP cam #: 1
- MAX IP cam # (licenses required): 20⁹

Photo Station

- Supported Image Format: BMP, JPG (jpe, jpeg), GIF, RAW (arw, srf, sr2, dcr, k25, kdc, cr2, crw, nef, mrv, ptx, pef, raf, 3fr, erf, mef, mos, orf, rw2, dng, x3f)
- Supported Video Format*: 3G2, 3GP, ASF, AVI, DAT, DivX, FLV, M4V, MOV, MP4, MPEG, MPG, QT, WMV, XviD, RM, RMVB, VOB, RV30, RV40, AC3, AMR, WMA3

Download Station

- Supported Download Protocols: BT/HTTP/FTP/NZB/eMule
- Custom BitTorrent Port Range
- BitTorrent / eMule Bandwidth Control

Audio Station

- Supported Audio Format: (USB Mode) AAC, FLAC, M4A, MP3, Ogg Vorbis, WMA, WMA VBR; (Streaming Mode) MP3, M4A, M4B
- Supported Playlist Format: M3U, WPL
- Internet Radio: SHOUTcast, Radioio

DLNA/UPnP Media Server

- PS3/Xbox 360 Support
- Supported Audio Format: AAC, FLAC, M4A, MP3, Ogg, Vorbis, PCM, WAV, WMA, WMA VBR, WMA PRO, WMA Lossless
- Supported Video Format: 3GP, 3G2, ASF, AVI, DAT, DivX, DVR-MS, ISO, M2T, M2TS, M4V, MKV, MP4, MPEG1, MPEG2, MPEG4, MTS, MOV, QT, SWF, TP, TRP, TS, VOB, WMV, XviD, RV30, RV40, AC3, AMR, WMA3
- Supported Image Format: BMP, JPG (jpe, jpeg), GIF, ICO, PNG, PSD, TIF (tiff), UFO, RAW (arw, srf, sr2, dcr, k25, kdc, cr2, crw, nef, mrv, ptx, pef, raf, 3fr, erf, mef, mos, orf, rw2, dng, x3f)

- Supported Subtitles Format: prt, srt, smi, ass, ssa, sub, idx,ifo

iTunes Server

- Supported Audio Format*: MP3, M4A, M4P, WAV, AIF
- Supported Video Format: M4V, MOV, MP4
- Supported Playlist Format: M3U, WPL

Printer Server¹¹

- Max Printer #: 2
- Printing Protocols: LPR, CIFS, AppleTalk

Synology Packages

- Mail Station
- Squeezebox Server
- Webalizer
- phpMyAdmin
- Time Backup
- HASP

iPhone/Android Applications

- DS photo+
- DS audio
- DS cam
- DS file (iPhone only)

General Specifications

Networking Protocols

- CIFS, AFP, FTP, iSCSI, Telnet, SSH, NFS, SNNP

File System

- EXT4
- EXT3 (External Disk Only)¹²
- FAT (External Disk Only)¹²
- NTFS (External Disk Read Only)¹²

Volume Management

- Synology Hybrid RAID
- iSCSI Target: 32
- iSCSI LUN: 256
- Volume Type: Basic, JBOD, RAID 0, RAID 1, RAID 5, RAID 5+Spare, RAID 6, RAID 10
- RAID Migration: from Basic to RAID 1, Basic to RAID 5, Basic to RAID 5+Spare, RAID 1 to RAID 5, RAID 1 to RAID 5+Spare, RAID 5 to RAID 5+Spare, RAID 5 to RAID 6
- Expand RAID 1, RAID 5, RAID 5+Spare or RAID 6 with Larger Hard Drives

File Sharing Capability

- Max User Account: 2048
- Max Group: 256
- Max Shared Folder: 256
- Max Concurrent Connections (SAMBA, FTP, AFP): 512

Windows ADS Domain Integration

- Domain Users login via Samba/AFP/FTP/File Station

Backup Solutions

- Network Backup
- Local Backup
- Desktop Backup (using Synology Data Replicator 3 or Apple Time Machine backup application)
- 3rd-Party Backup Support

Security

- FTP over SSL/TLS
- IP Auto-Block
- Firewall
- Encrypted Network Backup over Rsync
- HTTPS Connection

Management

- DSM Upgrade
- Email Notification
- SMS Notification
- Customized User Quota
- DDNS Support
- PPPoE
- Resource Monitor
- UPS Management
- Scheduled Power On/Off
- Custom Management UI HTTP/HTTPS Ports

HDD Management

- HDD Hibernation
- S.M.A.R.T.

- Dynamic Bad Sector Mapping

Utilities

- Synology Assistant
- Synology Download Redirector
- Synology Data Replicator 3

Support Browsers

- Internet Explorer 7
- Internet Explorer 8
- Firefox 3.6
- Safari 4 (Mac)
- Safari 5 (Mac)
- Chrome 8

Supported Clients

- Windows 2000 onward
- Mac OS X 10.3 onward
- Ubuntu 9.04 onward

Supported Mobile Devices (Photo Station, File Station)

- iPhone OS 2.2.1 onward
- Windows Mobile (IE Mobile or Opera 9.0 onward)
- Symbian OS 9.1, S60 3rd Edition onward

Language

- English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, Český, 日本語, 한국어, 繁體中文, 简体中文

Environment and Packaging

Environment

- RoHS Compliant

Package Content

- RS2211+/RS2211RP+ Main Unit
- Installation DVD

- Welcome Note
- Assembling Kit
- AC Power Cord

- RS2211+: x 1
- RS2211RP+: x 2

Optional Accessories

- Remote
- Camera License Pack
- Rail Kit
- L-type Mounting Brackets

SYNOLOGY INC.

Founded in 2000, Synology is a young and energetic company dedicated to developing high-performance, reliable, versatile, and environmentally-friendly Network Attached Storage (NAS) products. Our goal is to deliver user-friendly solutions and solid customer service to satisfy the needs of businesses, home offices, individual users and families.

Copyright © 2011, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan. RS2211+/RS2211RP+-2011-ENU-REV002

<http://www.synology.com>

Headquarters

Synology Inc.
3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan
Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

North & South America

Synology America Corp.
2899 152nd Ave NE, Redmond, WA 98052, USA
Tel: +1 425 818 1587

UK

Synology UK Ltd.
Davy Avenue, Knowlhill,
Milton Keynes, Bucks,
MK5 8PB, UK
Tel: +44 01908 673 709

1. Tested with Link Aggregation and 3GB RAM. The performance figures could vary on different environments.
2. Purchase separately.
3. RS2211+ supports up to one Synology RX1211 or RX1211RP
4. Hard drive not included.
5. Wireless dongles not included. Please check <http://www.synology.com> for supported wireless dongles.
6. The actual capacity will differ according to volume types.
7. Measured with 10 Western Digital 3TB WD30EZR5 hard drive. The figures could vary on different environments.
8. 1 free license to install 1 IP camera. Additional licenses can be purchased to expand the license quota.
9. User can click and download the following video formats: RM, RMVB, VOB, RV30, RV40, AC3, AMR, WMA3, but not able to play it in Photo Station as compressed Flash video.
10. The music in WAV and AIF format can be streamed, but the metadata (ex: title, album) may not be indexed on the iTunes.
11. For Mac users, RS2211+/RS2211RP+ supports PostScript USB printers only.
12. Primary partition only.

Networking

